## Coating Thickness Gauge (Statistical Type)





## **Principles**

Principles	Applications	Examples
F Type Magnetic Induction (Iron Base)	Measure the thickness of non-magnetic materials on magnetic materials	Galvanizing layer, lacquer layer, porcelain enamel layer, phosphide layer, copper tile, aluminium tile, some alloy tile, paper etc
NF Type Eddy Current (Aluminium Base)	Measure the thickness of non-conductive coatings on non- magnetic metals	Anodizing, varnish, paint, enamel, plastic coatings, powder, etc. Applied to aluminum, brass, non-magnetic stainless steel, etc

Model: RCM-1250 RCM-1250E

## Applications & Features

Coating thickness gauge is a kind of portable testing instrument, can take fast, intact, precise measurement of coating thickness. It can be used in both engineering field, and laboratories, as an essential instrument in material protection industry.

- \* Can store the new data in 99 groups.
- \* Metric/imperial system selectable.
- \* Manual or automatic power off.
- \* Auto memory of calibration value, auto substrate recognition.
- \* Use RS-232 data output to connect with PC.
- \* Provide Bluetooth data output choice.

## Specifications

Model	RCM-1250	RCM-1250E
Principle	F Magnetic Induction & NF Type Eddy Current	
Range	0~1250μm / 0~50mil	
Resolution	0.1μm / 1μm	
Accuracy	$\pm$ 1~3%n or $\pm$ 2.5 $\mu$ m	
Min. Radius Workpiece	F Type: convex 1.5 mm / concave 25 mm	
	NF Type: convex 3 mm / concave 50 mm	
Min. Measuring Area	6 mm	
Min. Sample Thickness	0.3 mm	
Metric / Imperial	√	
Battery Indicator	√	
Automatic Power Off	√	
Data Memory	99 Groups	
Operating Conditions	Temperature: 0~40°C	
	Humidity:	10~90%RH
Power Supply	2x1.5V AAA (UM-4) Battery	
Dimensions	126x65x35mm	
Weight	81g (Not Including Batteries)	

Standard Accessories	RCM-1250	RCM-1250E	
Main Unit	√	√	
Probe (F&NF Type)	Built-in	√	
Calibration Base (F)	√	√	
Calibration Base (NF)	√	√	
Calibration Foils	1 set, 5 pieces		
Carrying Case	B04		
Operation Manual	√		
Optional Accessories	RS-232C Data Cable with Software		
	Bluetooth Data Adapter with Software		